

Anshin-net 1

Command	Data type	Description	PS	AX	RW	Range
M_SSEC_MPANET1_CALLBACK_NUM1	T_STR	Telephone number to contact 1	--	--	RW	Within 28 letters
M_SSEC_MPANET1_CALLBACK_COM1	T_STR	Comment1	--	--	RW	Within 20 letters
M_SSEC_MPANET1_CALLBACK_NUM2	T_STR	Telephone number to contact 2	--	--	RW	Within 28 letters
M_SSEC_MPANET1_CALLBACK_COM2	T_STR	Comment2	--	--	RW	Within 20 letters
M_SSEC_MPANET1_CALLBACK_NUM3	T_STR	Telephone number to contact 3	--	--	RW	Within 28 letters
M_SSEC_MPANET1_CALLBACK_COM3	T_STR	Comment3	--	--	RW	Within 20 letters
M_SSEC_MPANET1_ENABLE_ANET	T_CHAR	Anshin-net enabled	--	--	RW	0,1
M_SSEC_MPANET1_ENABLE_KNET	T_LONG	MTB-net enabled	-	--	RW	0,1
M_SSEC_MPANET1_PASSWD	T_STR	Password in machining data share	-	-	RW	4 letters (Alphanumeric characters, excluding space)
M_SSEC_MPANET1_CUSTOMER_NUM	T_STR	Customer No. in machining data share	-	-	RW	8 letters (Alphanumeric characters, excluding space)